

PHILIPS

**5W (50W) GU5.3 cap Cool
daylight Non-dimmable
Spot**

929001240208



LEDspot, MR16, not dimmable, 50 W, GU5.3, 6500 K,
435 lm, 15000 hour(s)

LEDspot, MR16, not dimmable, 50 W, GU5.3, 6500 K, 435 lm, 15000 hour(s), 87 lm/W

General Information

Cap-Base	GU5.3
Nominal lifetime	15,000 hour(s)
Switching Cycle	50,000
Rated Lifetime (Hours)	15,000 hour(s)
Lighting Technology	LEDspot

Color Designation	Cool Daylight
Correlated Color Temperature (Nom)	6500 K
Luminous Efficacy (rated) (Nom)	87 lm/W
Color Consistency	<6
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %

Light Technical

Color Code	865 [CCT of 6500K]
Beam Angle (Nom)	24 degree(s)
Luminous Flux	435 lm
Luminous Intensity (Nom)	1,700 cd

Operating and Electrical

Line Frequency	- Hz
Input Frequency	- Hz
Power Consumption	5 W
Lamp Current (Nom)	580 mA
Wattage Equivalent	50 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	1 s
Power Factor (Fraction)	0.5
Voltage (Nom)	ac electronic 12 V

Temperature

T-Case Maximum (Nom)	76 °C
----------------------	-------


Controls and Dimming

Dimmable	No
----------	----

Mechanical and Housing

Overall length	47 mm
Overall width	50 mm
Overall height	46 mm
Dimensions (Height x Width x Depth)	46 x 50 x 47 mm
Bulb Shape	MR16
Net Weight (Piece)	0.045 kg

Dimensional drawing



Approval and Application

Suitable For Accent Lighting	Yes
EU RoHS compliant	Yes
Ambient temperature range	-20 to +45 °C

Application Conditions


Wireless Technology	Not applicable
---------------------	----------------

Product Data


Order product name	5W (50W) GU5.3 cap Cool daylight Non-dimmable Spot
Full product name	5W (50W) GU5.3 cap Cool daylight Non-dimmable Spot
Full product code	871869657957200
Order code	929001240208
Material Nr. (12NC)	929001240208
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718696579572
Numerator - Packs per outer box	10
EAN/UPC - Case	8718696579589

Product	D	C
5W (50W) GU5.3 cap Cool daylight Non-dimmable Spot	50 mm	46 mm

Photometric data




Spectral Power Distribution Colour - Essential LED 5-50W 6500K MR16 24D




Light Distribution Diagram - Essential LED 5-50W 6500K MR16 24D

Lifetime



Life Expectancy Diagram



Lumen Maintenance Diagram - Essential LED 5-50W 6500K MR16 24D

Related Documents

Documents and certificates	Document Name	Download
Environmental Product Declaration	Philips-Essential-LEDspot-MR16-COMF-6979519-Ref-929001239708-EPD.pdf	Download
Photometry and lighting design	Document Name	Download
IES File	LEDspots_GMGC_2_5W_MR16_GU5,3_865_24D-IES.IES	Download

